



# SAFETY DATA SHEET

RUBBOL WF 378

## 1. IDENTIFICATION OF THE SUBSTANCE/PREPARATION AND OF THE COMPANY/UNDERTAKING

- Product name and/or code** : RUBBOL WF 378
- Manufacturer/Distributor** : Akzo Nobel Industrial Coatings Ltd  
Unit 4a  
Mercer Way  
Shadsworth Business Park  
Blackburn  
Lancashire  
United Kingdom, BB1 2QZ  
Tel. Number: +44 (0) 1254 687950  
Fax Number: +44 (0) 1254 687960
- e-mail address of person responsible for this SDS** : industrial.msds@akzonobel.com
- Product use** : Waterborne coating for interior and exterior use.
- Emergency telephone number (with hours of operation)** : International Sikkens emergency number :  
Tel.: +31 71 3086944  
available 24 hours/day, every day of the week

## 2. HAZARDS IDENTIFICATION

The product is not classified as dangerous according to Directive 1999/45/EC and its amendments.

- Classification** : Not classified.
- Additional warning phrases** : Contains Polysiloxanes, modified. May produce an allergic reaction.

## 3. COMPOSITION/INFORMATION ON INGREDIENTS

There are no ingredients present which, within the current knowledge of the supplier and in the concentrations applicable, are classified as hazardous to health or the environment and hence require reporting in this section.

## 4. FIRST AID MEASURES

### First-aid measures

- General** : In all cases of doubt, or when symptoms persist, seek medical attention. Never give anything by mouth to an unconscious person.
- Inhalation** : Remove to fresh air. Keep person warm and at rest. If not breathing, if breathing is irregular or if respiratory arrest occurs, provide artificial respiration or oxygen by trained personnel. Give nothing by mouth. If unconscious, place in recovery position and seek medical advice.
- Skin contact** : Remove contaminated clothing and shoes. Wash skin thoroughly with soap and water or use recognised skin cleanser. Do not use solvents or thinners.

## 4. FIRST AID MEASURES

- Eye contact** : Check for and remove any contact lenses. Immediately flush eyes with running water for at least 15 minutes, keeping eyelids open.
- Ingestion** : If swallowed, seek medical advice immediately and show the container or label. Keep person warm and at rest. Do not induce vomiting.

## 5. FIRE-FIGHTING MEASURES

- Extinguishing media** : Recommended: alcohol-resistant foam, CO<sub>2</sub>, powders, water spray.  
Not to be used : water jet.
- Recommendations** : Fire will produce dense black smoke. Exposure to decomposition products may cause a health hazard. Appropriate breathing apparatus may be required. Cool closed containers exposed to fire with water. Do not release runoff from fire to sewers or waterways.

## 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions** : Due to the organic solvents content of the preparation:  
Exclude sources of ignition and ventilate the area. Avoid breathing vapour or mist. Refer to protective measures listed in sections 7 and 8.
- Spill** : Contain and collect spillage with non-combustible, absorbent material e.g. sand, earth, vermiculite or diatomaceous earth and place in container for disposal according to local regulations (see section 13). Do not allow to enter drains or watercourses. Preferably clean with a detergent. Avoid using solvents. If the product enters drains or sewers, immediately contact the local water company; in the case of contamination of streams, rivers or lakes, the relevant environment agency.

**Note:** see section 8 for personal protective equipment and section 13 for waste disposal.

## 7. HANDLING AND STORAGE

- Handling** : Due to the organic solvents content of the preparation:
- Vapours are heavier than air and may spread along floors. Vapours may form explosive mixtures with air. Prevent the creation of flammable or explosive concentrations of vapours in air and avoid vapour concentrations higher than the workplace exposure limits.
- In addition, the product should only be used in areas from which all naked lights and other sources of ignition have been excluded. Electrical equipment should be protected to the appropriate standard.
- Keep container tightly closed. Keep away from heat, sparks and flame. No sparking tools should be used.
- Avoid contact with skin and eyes. Avoid the inhalation of dust, particulates, spray or mist arising from the application of this preparation. Avoid inhalation of dust from sanding.
- Eating, drinking and smoking should be prohibited in areas where this material is handled, stored and processed. Workers should wash hands and face before eating, drinking and smoking.
- Put on appropriate personal protective equipment (see section 8).
- Never use pressure to empty. Container is not a pressure vessel. Always keep in containers made from the same material as the original one.
- Comply with the health and safety at work laws.
- When operators, whether spraying or not, have to work inside the spray booth, ventilation is unlikely to be sufficient to control particulates and solvent vapour in all

## 7. HANDLING AND STORAGE

cases. In such circumstances they should wear a compressed air-fed respirator during the spraying process and until such time as the particulates and solvent vapour concentration has fallen below the exposure limits.

### Storage

- : Store in accordance with local regulations. Observe label precautions. Store in a cool, well-ventilated area away from incompatible materials and ignition sources. Keep away from heat and direct sunlight.

Due to the organic solvents content of the preparation:

Keep away from: oxidising agents, strong alkalis, strong acids.

No smoking. Prevent unauthorised access. Containers that have been opened must be carefully resealed and kept upright to prevent leakage.

Do not empty into drains.

## 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

### Engineering measures

- : All engineering control measures used to control exposure to hazardous substances must be selected, maintained, examined and tested to meet the requirements of the Control of Substances Hazardous to Health Regulations (COSHH). Similarly all personal protective equipment, including respiratory protective equipment, must be selected, issued and maintained to meet the requirements of COSHH. These requirements include the provision of any necessary information, instruction and training with regard to their use. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead.

Provide adequate ventilation. Where reasonably practicable, this should be achieved by the use of local exhaust ventilation and good general extraction. If these are not sufficient to maintain concentrations of particulates and solvent vapours below the WEL, suitable respiratory protection must be worn.

### Workplace exposure limits

- : Not available.

### Personal protective equipment

#### Respiratory system

- : If workers are exposed to concentrations above the exposure limit, they must use appropriate, certified respirators.

Dry sanding, flame cutting and/or welding of the dry paint film will give rise to dust and/or hazardous fumes. Wet sanding/flattening should be used wherever possible. If exposure cannot be avoided by the provision of local exhaust ventilation, suitable respiratory protective equipment should be used.

#### Skin and body

- : Personnel should wear protective clothing.

#### Hands

Barrier creams may help to protect the exposed areas of the skin but should not be applied once exposure has occurred.

#### Eyes

- : Use safety eyewear designed to protect against splash of liquids.

### Environmental exposure controls

Do not allow to enter drains or watercourses.

## 9. PHYSICAL AND CHEMICAL PROPERTIES

<b>Physical state</b>	: Liquid.
<b>Flash point</b>	: Not applicable.
<b>Viscosity</b>	: Kinematic: 13,66 cm <sup>2</sup> /s (1366 cSt)
<b>Relative density</b>	: 1,171

## 10. STABILITY AND REACTIVITY

Stable under recommended storage and handling conditions (see section 7).

Hazardous decomposition products: carbon monoxide, carbon dioxide, smoke, oxides of nitrogen.

Keep away from the following materials to prevent strong exothermic reactions: oxidising agents, strong alkalis, strong acids.

## 11. TOXICOLOGICAL INFORMATION

There is no data available on the preparation itself. The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and classified for toxicological hazards accordingly. See sections 3 and 15 for details.

Exposure to component solvent vapour concentrations in excess of the stated workplace exposure limit may result in adverse health effects such as mucous membrane and respiratory system irritation and adverse effects on the kidneys, liver and central nervous system. Symptoms and signs include headache, dizziness, fatigue, muscular weakness, drowsiness and, in extreme cases, loss of consciousness. Solvents may cause some of the above effects by absorption through the skin. Repeated or prolonged contact with the preparation may cause removal of natural fat from the skin, resulting in non-allergic contact dermatitis and absorption through the skin. If splashed in the eyes, the liquid may cause irritation and reversible damage.

Contains Polysiloxanes, modified. May produce an allergic reaction.

### Acute toxicity

**Conclusion/Summary** : Not available.

### Chronic toxicity

**Conclusion/Summary** : Not available.

### Carcinogenicity

**Conclusion/Summary** : Not available.

### Mutagenicity

**Conclusion/Summary** : Not available.

### Teratogenicity

**Conclusion/Summary** : Not available.

### Reproductive toxicity

**Conclusion/Summary** : Not available.

## 12. ECOLOGICAL INFORMATION

There is no data available on the preparation itself.  
Do not allow to enter drains or watercourses.

The preparation has been assessed following the conventional method of the Dangerous Preparations Directive 1999/45/EC and is not classified as dangerous for the environment.

### Aquatic ecotoxicity

**Conclusion/Summary** : Not available.

### Biodegradability

## 12. ECOLOGICAL INFORMATION

**Conclusion/Summary** : Not available.

## 13. DISPOSAL CONSIDERATIONS

Do not allow to enter drains or watercourses.

Dispose of according to all federal, state and local applicable regulations.

**Hazardous waste** : Within the present knowledge of the supplier, this product is not regarded as hazardous waste, as defined by EU Directive 91/689/EEC.

## 14. TRANSPORT INFORMATION

**Transport within user's premises:** always transport in closed containers that are upright and secure. Ensure that persons transporting the product know what to do in the event of an accident or spillage.

### Sea

**Special provisions** : Not available.

**Marine pollutant** : No.

### Air

**Special provisions** : Not available.

The "viscosity exemption" provisions do not apply to air transport.

**This product is not regulated for carriage according to ADR/RID, IMDG, ICAO/IATA.**

## 15. REGULATORY INFORMATION

**EU regulations** : The product is determined as not being dangerous according to the requirements of the DPD.

**Risk phrases** : This product is not classified according to EU legislation.

**Safety phrases** : S2- Keep out of the reach of children.  
S46- If swallowed, seek medical advice immediately and show this container or label.

**Additional warning phrases** : Contains Polysiloxanes, modified. May produce an allergic reaction.

## 16. OTHER INFORMATION

**CEPE Classification** : 2

The information in this Safety Data Sheet is required pursuant to EU Directive 91/155/EEC and its amendments.

The information contained in this safety data sheet is provided in accordance with the requirements of the CHIP Regulations.

Further information and relevant advice can be found in:

- The Control of Substances Hazardous to Health Regulations (As amended).
- The Manual Handling Operations Regulations (As amended).
- The Environmental Protection (Duty of Care) Regulations (As amended).
- 'EH40 : Workplace exposure limits.

**Date of issue/Date of revision** : 18-2-2009.

**Version** : 2

**Notice to reader**

## 16. OTHER INFORMATION

### **FOR PROFESSIONAL USE ONLY**

**IMPORTANT NOTE** *The information in this data sheet is not intended to be exhaustive and is based on the present state of our knowledge and on current laws: any person using the product for any purpose other than that specifically recommended in the technical data sheet without first obtaining written confirmation from us as to the suitability of the product for the intended purpose does so at his own risk. It is always the responsibility of the user to take all necessary steps to fulfill the demands set out in the local rules and legislation. Always read the Material Data Sheet and the Technical Data Sheet for this product if available. All advice we give or any statement made about the product by us (whether in this data sheet or otherwise) is correct to the best of our knowledge but we have no control over the quality or the condition of the substrate or the many factors affecting the use and application of the product. Therefore, unless we specifically agree in writing otherwise, we do not accept any liability whatsoever for the performance of the product or for any loss or damage arising out of the use of the product. All products supplied and technical advice given are subject to our standard terms and conditions of sale. You should request a copy of this document and review it carefully. The information contained in this data sheet is subject to modification from time to time in the light of experience and our policy of continuous development. It is the user's responsibility to verify that this data sheet is current prior to using the product.*

*Brand names mentioned in this data sheet are trademarks of or are licensed to AkzoNobel.*

### **Head Office**

**Akzo Nobel Decorative Coatings B.V, Rijksstraatweg 31, 2171 AJ Sassenheim, the Netherlands**